

Biolith tiles are a revolutionary material that is made by harnessing **the power of biology** to form Biocement[®]. Biocement technology uses bacteria and nutrients to produce calcium carbonate, which cements aggregate together. This process happens in ambient temperatures, without the use of a kiln.


Our Biolith tile can be used in vertical facing assemblies, installed on a support wall with adhesive or mechanical systems, or used on a substrate in horizontal conditions. Our tiles meet building standard requirements for compressive strength, absorption, adhesion, and dimensional tolerance. Biolith tiles are ideal for use in commercial, institutional, and residential building projects.

COLOR



Peppercorn





SUSTAINABILITY

Biolith tiles have many sustainability features applicable to different building rating systems. This includes LEED v4.1, WELL v2, BREEAM, and DGNB. Detailed list available upon request.

Applicable certifications/declarations:

- HPDv2.1
- Declare Red List Free
- Various 3rd Party Test Data

©2023 Biomason, Inc. All rights reserved. Biomason®, Biolith®, and Biocement® are registered trademarks of Biomason, Inc. registered in the US. 230316_AH



sales@biomason.com www.biomason.com 1-80-BIOMASON ext. 2 ା

in


y

PRODUCT DATA

	Product code		Metric		
Size	4020		400 mm x 200 mm x 19 mm		
	4004		400 mm x 40 mm x 19 mm		
Grout Spacing	(All)		3 mm - 13 mm		
Color	Peppercorn				
Finishes	Honed, Polished				
Strength (minimum performance)	Compressive	30 MPa		Flexural	> 4 MPa

*Contact us for additional sizes. Minimum order quantities apply.

PROCESS





Aggregate

Biolith® Tile



INSTALLATION + MAINTENANCE

- Installs like traditional tile when using thin-set mortar • (installation manual available upon request)
- Clean Biolith tiles in accordance with the guidelines in the Care and Maintenance Plan. Never use acid-based cleaners, such as hydrochloric or muriatic acid, on Biolith tiles.

RECOMMENDED USES



BI^oMason

Biolith® tiles are natural products. Variations in color, shade, and surface shading among tiles should be expected. Images shown may not indicate all of these variations accurately. It is recommended that you order a physical sample prior to placing an order, but note that variation across different tiles is expected and physical sample is not indicative of all possible variations in above characteristics.